OKLAHOMA DEPARTMENT OF TRANSPORTATION

FED. ROAD DIST. NO.	STATE	JOB PIECE NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	OKLA.				

REVISIONS

DESCRIPTION	DATE

N 00°27'55.84" E 2637.47'
NS-212.5

N 00°27'55.84" E 2624.45'

N 88°59'18.48" W 2643.82'

S 89°16'53.54" E 2638.75'

MATCH LINE 365+00

370+00

375+00

380+00

385+00

390+00

PC 382+42.72
382+42.72 PER FAS No S-413(3) SH PLANS

PI 389+49.52

CURVE - 1
PI=389+49.52
Δ=40°37'00.00" Rt
D0C=3°00'00.00"
T=706.79'
L=1353.89'
R=1909.86'
C=1325.72'
N 2°10'15.00" E
RAD PT 302

SCALE OF FEET
0 100 200 300

9014 9019 9006 9015 9011 9007 9016 9020 9008

7694 7400 317 7601 7638 7639 7640 7637 7641 7642 7602 7603 7650 7658 7653 7652 7651 7604 7605 7606

SET 2" ALUM CAP IN CONC STAMPED "7400"

SET MAG NAIL/CA3949 TAG

N 00°51'45.00" E
℄ SURVEY - S.H. 44 A001

PRES.R/W
N 00°51'45.00" E 1165.72'
NS-213

N 00°25'23.88" E 2638.23'

N 89°08'15.00" W 10.00'

78.63'
N 00°51'45.00" E

246.37'
N 00°51'45.00" E

S 89°08'15.00" E 18.25'

N 97°00'00" W 50'

2357.65'

N 00°23'58.73" E 2637.24'

FOUND 1/2" IP

1532.56'

SET MAG NAIL /CA3949 TAG

R=1849.86'
N 03°38'28.19" E
C=179.35'
L=179.42'

C-1
RAD PT

R=1969.86'
N 28°28'57.16" E
C=1145.56'
L=1200.41'

R=1849.86'
N 23°56'58.19" E
C=1114.35'
L=1131.93'

PT 395+96.61
395+96.61 PER FAS No S-413(3) SH PLANS

N 29°41'15.00" W
R=479.80'
C=309.17'
L=315.42'
RAD PT 7655

N 48°15'15.00" W 140.00'

SET MAG NAIL/CA3949 TAG

N 41°28'45.00" E
℄ SURVEY - S.H. 44 A001
283.39'
PRES.R/W

S 78°13'25.05" E 506.58'
PRES.R/W (CHANNEL)

MATCH LINE
400+00

S 89°16'53.49" E 2638.72'

EW-131.5
S 89°33'50.02" E 2645.12'

EW-132
N 89°24'34.62" W 2652.72'

EW-132
N 89°24'34.62" W 2643.82'

EW-132 (STATUTORY R/W)
S 88°59'18.48" E 2340.58'

BEGIN SURVEY 370+77.00
AS SHOWN ON FAS No.S-413 (3) SH PLANS

POT 357+83.40
℄ SH 44 AND SEC LINE 3.46' Rt
3.8' Rt PER FAS No S-413(3) SH Plans

360+00

POT 362+34.64
℄ SH 44 AND SECTION CENTER
451.57' SOUTH TO SECTION CORNER
2186.66' NORTH TO 1/4 SECTION CORNER

365+00

POC 384+21.68
384+22 PER FAS No S-413(3) SH PLANS
25.14' LT TO 1/4 CORNER (17.3' LT PER PLANS)
2619.98' Rt TO SECTION CENTER (NO O/S PER PLANS)

MATCH LINE 370+00

N 00°51'45.00" E
℄ SURVEY - S.H. 44 A001

N 00°51'45.00" E 1202.00'
PRES.R/W

PRES.R/W
N 00°51'45.00" E 1202.00'

N 89°08'15.00" W 240.00'

S 89°08'15.00" E 240.00'

N 00°51'45.00" E 58.13'

N 00°51'45.00" E 57.52'

EW-132
N 89°24'34.62" W 2652.72'

N 89°24'34.62" W 2355.83'

312 311 301 300 9015 7636 7600 7649 7648 7632 7633

NS-213.5
N 00°15'32.37" E 2645.40'

N 00°15'32.37" E 2624.23'

NOTE:
ALL REFERENCE POINTS ARE 1/2" IRON PINS UNLESS OTHERWISE NOTED ON SURVEY.

PLS	CRS	12/12	OKLAHOMA DEPARTMENT OF TRANSPORTATION SURVEY DIVISION
DRAWN	TDL	12/12	SMITH ROBERTS BALDISCHWILER, LLC 100 N.E. 5th Street, Oklahoma City, OK 73104 Telephone:(405) 840-7094 FAX:(405) 840-9116
CHECKED	JAC	12/12	SURVEY DATA SHEET
APPROVED	CRS	12/12	
CREW	BC, SG, BH		SWO 4836 (1) PROJECT NO. 28999(04) SHEET NO. SD 08

SDS 8 OF 14