GENERAL NOTES- HISTORICAL BRIDGE SIGNAGE

VINYL ART PANEL NOTES:

VINYL ART PANELS SHALL BE FULL—COLOR, FABRICATED TO THE NOMINAL DIMENSIONS SHOWN, AND CONFIRMED TO FIT WITHIN THE DISPLAY CASES PRIOR TO FABRICATION.

CONTENT ON VINYL ART PANELS TO BE PROVIDED IN HIGH-RESOLUTION DIGITAL FORMAT TO THE CONTRACTOR BY THE OKLAHOMA DEPARTMENT OF TRANSPORTATION ENVIRONMENTAL PROGRAMS DIVISION. CONTACT SCOTT SUNDERMEYER AT (405) 325-7201.

DISPLAY CASE NOTES:

DISPLAY CASES SHALL BE SPECIFIED FOR OUTDOOR USE.

DISPLAY CASES SHALL CONSIST OF A RECTANGULAR BOX WITH SATIN ALUMINUM FRAME AND SINGLE—PANEL WINDOW DOOR WITH SATIN ALUMINUM FRAME.

CASE SHALL BE MOUNTED TO HSS 21/2"x11/2"x1/18" HORIZONTAL MEMBERS.

CASE SHALL BE WEATHER-PROOF AND VENTILATED TO PREVENT CONDENSATION FROM FORMING.

CASE WILL NOT BE SELF-ILLUMINATED.


DOOR SHALL CONTAIN A SHATTER-RESISTANT GLASS, ACRYLIC, OR POLYCARBONATE PANEL WITH A KEYED LOCK. DOOR SHALL BE CONNECTED TO THE CASE WITH FULL-LENGTH PIANO HINGE.

HISTORICAL BRIDGE SIGNAGE STRUCTURE:

HISTORICAL BRIDGE SIGNAGE STRUCTURE IS COMPRISED OF THE HOLLOW STRUCTURAL SECTION (HSS) RECTANGULAR MEMBERS, STEEL PEDESTALS, BASE PLATES, ANCHOR BOLTS, CLASS A CONCRETE FOOTING, AND REINFORCING STEEL.

HSS RECTANGULAR MEMBERS SHALL BE PROVIDED IN ACCORDANCE WITH ASTM A500 GRADE B. STEEL PLATES SHALL COMPLY WITH AASHTO M270, GRADE 50. ANCHOR BOLTS SHALL COMPLY WITH ASTM F1554, GRADE 55, WITH COMPATIBLE NUTS AND WASHERS.

ALL EXPOSED STEEL, INCLUDING BASE PLATES AND ANCHOR BOLTS SHALL HAVE A BLACK, POWDER-COATED PAINT FINISH.





DAVID M. NEUHAUSER, P.E. OKLA. REG. NO. 19980

DESIGN:	CPY	BRIDGE "A"	LOGAN COUNTY
DRAWN:	CPY	GENERAL NOTES AND	CLIMALARY
CHECKED:	CPY		SUMMARY
APPRVD:	CPY	OF PAY QUANTITIES	(BRIDGE)
CDU		(SHEET 4 OF	4)
	& 1 3	STATE JOB PIECE NO: 21860(04)	SHEET NO.ABO4