

**TRAFFIC SIGNING GENERAL CONSTRUCTION NOTES**

REMOVED MATERIAL TO BECOME PROPERTY OF CONTRACTOR AND IT SHALL BE DISPOSED OF IN A MANNER APPROVED BY THE ENGINEER.

ANY DAMAGE CAUSED BY THE CONTRACTOR TO ANY STRUCTURES, ROADWAY SURFACES, STRIPING, RAISED PAVEMENT MARKERS, GUARDRAIL, SLOPES, AND SIGNS SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE ENGINEER.

ALL REGULATORY SIGNS SHALL HAVE HIGH INTENSITY SHEETING. THE HIGH INTENSITY SHEETING SHALL MEET THE REQUIREMENTS OF ASTM D4956-(LATEST REVISION) FOR TYPE III SHEETING.  
ALL WARNING SIGNS SHALL HAVE FLUORESCENT YELLOW SHEETING. THE FLUORESCENT YELLOW SHEETING SHALL MEET THE REQUIREMENTS OF ASTM D4956-(LATEST REVISION) REQUIREMENTS FOR TYPE VIII SHEETING.

ALL GREEN AND BLUE SIGNS ON CONVENTIONAL HIGHWAYS SHALL HAVE HIGH INTENSITY SHEETING. THE HIGH INTENSITY SHEETING SHALL MEET THE REQUIREMENTS OF ASTM D4956-(LATEST REVISION) FOR TYPE III SHEETING.

ALL PANEL AND OVERHEAD SIGNS SHALL HAVE TYPE III HIGH INTENSITY BACKGROUND WITH TYPE VIII LEGENDS AND BORDERS. THE TYPE III BACKGROUND AND THE TYPE VIII LEGENDS AND BORDERS SHALL MEET THE REQUIREMENTS OF ASTM D4956-(LATEST REVISION). THE MANUFACTURER SHALL FURNISH A TYPE 'A'. CERTIFICATION IN ACCORDANCE WITH ODOT STANDARD SPECIFICATIONS, LATEST EDITION, AND SUBSECTION 106.04. THE CERTIFICATION SHALL INCLUDE TEST RESULTS ON THE MATERIAL SUBMITTED FOR APPROVAL.

THE CONTRACTOR IS RESPONSIBLE FOR THE PROMPT REPLACEMENT AND/OR REPAIR OF ALL TRAFFIC CONTROL DEVICES AND APPURTENANCES DAMAGED OR DISTURBED DUE TO CONSTRUCTION.

NO SPLICES SHALL BE PERMITTED IN ANY PIPE OR WIDE FLANGE SIGN POSTS.

ALL ANCHOR BOLTS SHALL BE GRADE A-36 STEEL.

THE STATIONS AND LOCATIONS OF THE SIGN PLACEMENT, AS SHOWN ON THE PLAN SHEETS, ARE APPROXIMATE. EXACT STATIONS AND LOCATIONS SHALL BE DETERMINED BY THE CONTRACTOR SO THAT THE SIGN IS INSTALLED IN ACCORDANCE WITH DEPARTMENT STANDARDS AND THE MUTCD IN ORDER TO PROVIDE OPTIMUM VISIBILITY TO THE ONCOMING/APPROACHING MOTORIST. IF A PROPOSED LOCATION CONFLICTS WITH OTHER SIGNS, UTILITIES OR OTHER ROADWAY FEATURES, THE ENGINEER SHALL BE NOTIFIED.

POST LENGTHS SHOWN ON SIGN SUMMARY ARE APPROXIMATE, EXACT LENGTH SHALL BE DETERMINED BY FIELD SURVEY BY THE CONTRACTOR.

THE CONTRACTOR IS RESPONSIBLE FOR THE REMOVAL OF ALL PAVEMENT MARKINGS THAT WILL BE IN CONFLICT WITH THE PROPOSED WORK.

AFTER REMOVAL OF ANY SIGN FOOTINGS, THE HOLES SHALL BE FILLED WITH SOIL AND TAMPED AND SHAPED IN A MANNER APPROVED BY THE ENGINEER.

A WORK ZONE PERMIT MUST BE OBTAINED FROM THE CITY OF NORMAN TRAFFIC DIVISION AT LEAST TWO (2) WORKING DAYS PRIOR TO THE START OF WORK AND/OR PLACING OR REMOVING ANY BARRICADES OR MODIFYING EXISTING TRAFFIC CONTROL DEVICES. CALL (405) 329 0528 TO OBTAIN AN APPLICATION.

**TRAFFIC SIGNING PAY QUANTITY NOTES**

- (TS-11) QUANTITY SHOWN INCLUDES 2,137.00 L.F. TRAFFIC STRIPE (PLASTIC) (WHITE) AND 0.00 L.F. TRAFFIC STRIPE (PLASTIC) (YELLOW) AND WILL BE MEASURED BY THE LINEAR FOOT OF FOUR INCH (4") WIDE TRAFFIC STRIPE. THIS STRIPE SHALL BE APPLIED AT A THICKNESS OF 70 MILS, IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND APPROVAL BY THE ENGINEER.
- (TS-14) QUANTITY SHOWN INCLUDES 504.00 L.F. TRAFFIC STRIPE (PLASTIC) (WHITE) AND 0.00 L.F. TRAFFIC STRIPE (PLASTIC) (YELLOW) AND WILL BE MEASURED BY THE LINEAR FOOT OF FOUR INCH (24") WIDE TRAFFIC STRIPE. THIS STRIPE SHALL BE APPLIED AT A THICKNESS OF 70 MILS, IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND APPROVAL BY THE ENGINEER.
- (TS-24) QUANTITY SHOWN INCLUDES 2,507 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(WHITE) AND 1,970 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(YELLOW) AND WILL BE MEASURED BY THE LINEAR FOOT OF FOUR INCH (4") WIDE TRAFFIC STRIPE.
- (TS-25) QUANTITY SHOWN INCLUDES 2,577 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(WHITE) AND 0.00 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(YELLOW) AND WILL BE MEASURED BY THE LINEAR FOOT OF FOUR INCH (4") WIDE TRAFFIC STRIPE
- (TS-26) QUANTITY SHOWN INCLUDES 0 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(WHITE) AND 601 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(YELLOW) AND WILL BE MEASURED BY THE LINEAR FOOT OF EIGHT INCH (8") WIDE TRAFFIC STRIPE.
- (TS-28) QUANTITY SHOWN INCLUDES 178 L.F. TRAFFIC STRIPE (MULTI-POLYMER)(WHITE) AND WILL BE MEASURED BY THE LINEAR FOOT OF TWENTY-FOUR INCH (24") WIDE TRAFFIC STRIPE.
- (TS-33) INCLUDED IN THIS PAY ITEM IS ALL HARDWARE ASSOCIATED WITH PROPERLY ANCHORING AND MOUNTING THE HIGHWAY SIGN IN ACCORDANCE WITH O.D.O.T. PLANS AND STANDARD DRAWINGS SSA1-1-(LATEST REVISION) AND SSP1-1-(LATEST REVISION).
- (TS-34) INCLUDED IN THIS PAY ITEM IS THE REMOVAL OF ANY EXISTING SIGNS TO BE REPLACED BY NEW ASSEMBLIES AND THE REMOVAL OF ANY EXISTING SIGNS THAT WILL BE IN CONFLICT WITH THE NEW ROADWAY OR NEW SIGNAGE.
- (TS-41) REMOVAL OF EXISTING SIGNS\* SHALL INCLUDE THE REMOVAL OF A COMPLETE SIGN ASSEMBLY WHICH MAY INCLUDE MULTIPLE SIGNS, POSTS, FOOTINGS, AND ANY FOOTINGS ADJACENT TO THE SIGN ASSEMBLY. WHEN APPROVED BY THE ENGINEER, FOOTINGS MAY BE OBLITERATED TO A POINT BELOW GROUND LEVEL IN LIEU OF BEING COMPLETELY REMOVED. SEE GENERAL CONSTRUCTION NOTES FOR DISPOSAL OF OLD CONCRETE FOOTING MATERIAL.

**TRAFFIC CONTROL PAY QUANTITY NOTES**

- (TC-16) PAINT SHALL CONFORM TO SECTION 711 "TRAFFIC STRIPE", OF THE O.D.O.T. STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).  
IF CONSTRUCTION TRAFFIC STRIPE PAINT IS INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND FAILS DURING THE FIRST SIX MONTHS OF SERVICE, REPLACEMENT WILL BE MADE AT THE CONTRACTOR'S EXPENSE AND SHALL BE ACCOMPLISHED IN A TIMELY MANNER UPON NOTIFICATION BY THE ENGINEER OF SUCH FAILURE. (NOTE FOR CONSULTANT OR DESIGNER: THIS NOTE SHALL BE USED ON ROADWAY PROJECTS WITH ADT GREATER THAN 10,000)
- (TC-17) INCLUDES AN ESTIMATED 4,790 L.F. (PAINT)(4" WIDE) WHITE 4,790 L.F. (PAINT)(4" WIDE) YELLOW STRIPE.
- (TC-20) ALL STRIPING TO BE PLACED ON TEMPORARY SURFACES OR ON SURFACES SCHEDULED TO BE REMOVED SHALL BE DONE WITH PAINT UNLESS OTHERWISE NOTED ON THE PLANS OR STANDARD DRAWINGS. TEMPORARY PAVEMENT MARKINGS PLACED ON FINISHED PAVEMENT OR EXISTING PAVEMENT TO REMAIN IN PLACE SHALL USE ONE OF THE FOLLOWING METHODS:
  - REMOVABLE PAVEMENT MARKING TAPE
  - CLASS A PAVEMENT MARKERS
- (TC-21) INCLUDED IN THE COST OF THIS ITEM SHALL BE INSTALLATION, MAINTENANCE, AND REMOVAL. THIS ITEM SHALL BE BID ACCORDINGLY.
- (TC-22) AMOUNT SHOWN IS AN APPROXIMATION AND THE ACTUAL AMOUNT OF REMOVAL, IF NECESSARY, SHALL BE DETERMINED BY THE ENGINEER. PRICE BID FOR PAVEMENT MARKING REMOVAL SHALL INCLUDE THE COST OF REMOVING STRIPE, ARROWS, WORDS AND SYMBOLS, AS SHOWN IN THE PLANS. THESE ITEMS MAY CONSIST OF PLASTIC, PAINT OR NON-REMOVABLE MARKING TAPE.
- (TC-26) ALL CONSTRUCTION TRAFFIC CONTROL WILL BE IMPLEMENTED ACCORDING TO CONSTRUCTION PLANS, AND INSTALLED IN A MANNER APPROVED BY THE ENGINEER, IN ACCORDANCE WITH CHAPTER VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, (CURRENT EDITION), AND COMPLIANT WITH APPLICABLE O.D.O.T. STANDARD DRAWINGS. PRICE BID FOR THIS ITEM SHALL BE PAYMENT IN FULL FOR THE INSTALLATION, MAINTENANCE AND SUBSEQUENT REMOVAL OF ALL NECESSARY CONSTRUCTION TRAFFIC CONTROL DEVICES REQUIRED FOR COMPLETION OF THE PROJECT.
- (TC-33) ALL CONSTRUCTION WORK ZONE SIGNS SHALL HAVE FLUORESCENT SHEETING. THE FLUORESCENT SHEETING SHALL MEET THE REQUIREMENTS OF ASTM D4956 (LATEST REVISION)
- (TC-61) ANY DAMAGE TO A FINISHED OR EXISTING SURFACE RESULTING FROM THE CONTRACTORS NEGLIGENCE IN THE REMOVAL OF CONSTRUCTION ZONE PAVEMENT MARKERS OR CHANNELIZING DEVICES AND THE BITUMINOUS ADHESIVE USED IN THEIR INSTALLATION, SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE AND TO THE SATISFACTION OF THE ENGINEER.
- (TC-70) THIS ITEM IS AN ESTIMATED QUANTITY TO BE USED AS DEEMED NECESSARY BY THE ENGINEER.
- (TC-73) QUANTITY SHOWN INCLUDES 368 EA. (WHITE) AND 368 EA. (YELLOW) CONSTRUCTION ZONE PAVEMENT MARKERS (FLEX TABS). THESE CONSTRUCTION ZONE PAVEMENT MARKERS SHALL BE EITHER "DAVIDSON PLASTICS: MODEL TOM", OR AN APPROVED EQUAL. PRICE BID FOR THIS ITEM SHALL INCLUDE THE INITIAL PLACEMENT, SUBSEQUENT REPLACEMENT, AND REMOVAL. THE CONSTRUCTION ZONE PAVEMENT MARKERS (FLEX TABS) SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND AS SHOWN ON STANDARD DRAWING TCS21-1-(LATEST REVISION).
- (TC-75) TEMPORARY PAVEMENT MARKINGS SHALL BE IN PLACE THE SAME DAY THAT EXISTING PAVEMENT MARKINGS ARE REMOVED FROM ANY ROADWAY OPEN TO TRAFFIC. ALSO, ALL TEMPORARY PAVEMENT MARKINGS SHALL BE REMOVED PRIOR TO THE INSTALLATION OF FINAL STRIPING.
- (TC-84) 140 CONSTRUCTION CALENDAR DAYS WERE USED TO COMPUTE THE SIGN DAY PAY ITEMS. THE AMOUNT OF CALENDAR DAYS USED TO COMPUTE THE SIGN DAY PAY ITEMS IS AN ESTIMATED QUANTITY ONLY, BASED ON THE CURRENT ODOT STANDARDS AND SUGGESTED CONSTRUCTION SEQUENCE FOR THIS PROJECT. THESE ESTIMATED SIGN DAY QUANTITIES MAY CHANGE AS THE PROJECT'S CONSTRUCTION TRAFFIC CONTROL IS MODIFIED DURING CONSTRUCTION.

0301 PAY QUANTITIES				
SIGNING AND STRIPING				
ITEM NO.	CODE NO.	DESCRIPTION	UNITS	QUANTITY
805(A)	8724	(PL)REMOVAL OF EXISTING SIGNS	(TS-41) EA	24.00
850(A)	8110	SHEET ALUMINUM SIGNS	(TS-34) SF	142.00
851(C)	8324	2" SQUARE TUBE POST	(TS-33) LF	246.00
855(A)	8812	TRAFFIC STRIPE(PLASTIC)(4" WIDE)	(TS-11) LF	2,137.00
855(A)	8825	TRAFFIC STRIPE(PLASTIC)(24" WIDE)	(TS-14) LF	504.00
855(B)	3300	TRAF_STR(PLAST)(SYMBOLS, WORDS, ETC)	EA	14.00
856(A)	8530	TRAFFIC STRIPE(MULTIPOLY)(4" WIDE)	(TS-24) LF	4,477.00
856(A)	8535	TRAFFIC STRIPE(MULTIPOLY)(8" WIDE)	(TS-25) LF	2,577.00
856(A)	8540	TRAFFIC STRIPE(MULTIPOLY)(8" WIDE)	(TS-26) LF	601.00
856(A)	8555	TRAF. STRIPE(MULTIPOLY)(24" WIDE)	(TS-28) LF	178.00
856(B)	8525	TRAF_STR(MULTIPOLY)(SYM,WRD,ETC)	EA	45.00

0302 PAY QUANTITIES				
TRAFFIC CONTROL				
ITEM NO.	CODE NO.	DESCRIPTION	UNITS	QUANTITY
857(A)	8839	CONSTRUCTION TRAFF_STR(PAINT)(4" WIDE)	(TC-16,17,20,70,75) LF	9,580.00
857(E)	8890	(PL)CONST.ZONE PAV.MKRS(FLEX TAB)TYP.2-2	(TC-21,61,70,73,75) EA	736.00
857(F)	8006	PAVEMENT MRKNG.REMOVAL(TRAF_STRP)	(TC-22,70,75) LF	9,580.00
880(B)	8818	CONSTRUCTION SIGNS 0 TO 6.25 SF	(TC-21,33) SD	350.00
880(B)	8821	CONSTRUCTION SIGNS 6.26 SF TO 15.99 SF	(TC-21,33) SD	2,485.00
880(B)	8824	CONSTRUCTION SIGNS 16.0 SF TO 32.99 SF	(TC-21,33) SD	2,830.00
880(C)	8842	CONSTRUCTION BARRICADES(TYPE II)	(TC-26,84) SD	1,680.00
880(E)	8860	WARNING LIGHTS(TYPE A)	(TC-26,84) SD	2,270.00
880(F)	8878	DRUMS	(TC-26,84) SD	51,360.00

2/16/2017 5:15:10 PM - P:\8881\2131-08512-300\CAD\SHEETFILES\TRAFFIC\TRAFFIC.DWG - RODRIGUEZ, ANY