


- NOTES:**
- FOR CLARITY, SLOPE DESIGNATIONS SHOWN ON THE CROSS SECTION SHEETS ARE LISTED AS RUN:RISE.
  - EXISTING RAIL BALLAST BEGINS AT APPROXIMATE STA. 533+11. AGGREGATE BASE CALCULATED AT 6" DEPTH TO STA. 533+11.
  - AGGREGATE BASE MATERIAL SHALL BE PLACED AS A CONTINGENCY ONLY FROM STA. 533+11 - STA. 616+34.86 IF THE EXISTING RAIL BALLAST DOES NOT MEET COMPACTION REQUIREMENTS.
  - EXCESS CUT VOLUMES OF RAIL BALLAST MATERIAL GENERATED BY EARTHWORK OPERATIONS MAY BE WASTED ALONG THE RAIL BALLAST SIDE SLOPES AS APPROVED BY THE ENGINEER. BALLAST SIDE SLOPES SHALL BE GRADED SMOOTH AND LEFT IN A MAINTAINABLE CONDITION.

F:\681 Osage Prairie Trail\Ext\Final\CAD BASE Files\From Road\Calc363\X-Sections\vc012001R1.dwg, 6/15/2017 10:53:43 AM



Osage Prairie Trail Extension		
Design	JM	8/16
Drawn	JM/BB	8/16
Checked	JM/KF	6/17
Approved		
Squad	LPCI	

PREPARED BY:  
**LANDPLAN CONSULTANTS**  
1110 West 23rd Street TULSA, OK 74107 918-584-6464

**CROSS SECTIONS (1)**