


NOTE: STREET LIGHT WIRING

ONE PAIR EQUALS TWO CONDUCTORS (1/C-10AWG COPPER) ONE BLACK, ONE WHITE. CONDUCTORS SHALL BE SPLICED ONLY AT THE TERMINAL BLOCK AT EACH POLE. BASE. A FUSE HOLDER SHALL BE PROVIDED IN THE HANDHOLE OF EACH COMBINATION TRAFFIC SIGNAL AND STREET LIGHT POLE. THE FUSE HOLDER SHALL BE INSTALLED IN THE LINE SIDE CONDUCTOR FOR THE LUMINAIRE. THE FUSE HOLDER SHALL BE A WATERPROOF INLINE FUSE HOLDER. IT SHALL BE SIMILAR TO BUSSMAN WFG. CO. TYPE "TRON" HEB. OR OTHER APPROVED EQUAL, COMPLETE WITH A PROPERLY SIZED TYPE KTK FUSE.

YEAR	STATE JOB NO.
2017	33078 (04)



MOLSSON ASSOCIATES
 Olson Associates - Civil Engineering
 Oklahoma Certified as of February 26, 2013
 702 S. Main Street
 Joplin, MO 64801
 TEL 417.795.1694
 FAX 417.795.1714
 www.olsonassociates.com

REV. NO.	DATE	REVISIONS DESCRIPTION

SIGNAL WIRING DIAGRAM
WO#7 - TRAFFIC SIGNAL PLANS
 MAIN STREET AND STEVE OWENS BOULEVARD
 CITY OF MIAMI, OKLAHOMA
 MIAMI, OKLAHOMA
 2017

drawn by:	
checked by:	
approved by:	
project no.:	016-2300 W07
drawing no.:	SEE PLOT STAMP
date:	07-18-2017