

18. SUBMISSION OF SURVEY DATA

- A. Historical Letter and Written Report
- B. Form SD 1 – Transmittal Letter
- C. Form SD 7 – Public and Private Owned Utilities List
- D. (2) Form SD 11 – Position and Description of Project Control Monuments
- E. Form SD 20 – Survey Control Data Statement
- F. Form SD 41 – Surveyors Certificate
- G. Copies of Oklahoma Certified Corner Records (Originals will be filed with the Oklahoma Department of Libraries)
- H. Benchmarks and Check Levels List
- I. COGO Data and Alignment Report

DETAILED NARRATIVE OF SECTION CORNER ASSESSMENT

- C-18-463 Northwest Corner of Section 28, Township 28 North, Range 20 East, established corner from proportionate measurements, incorporating the Northwest Corner of Section 21 and the Southwest Corner of Section 28 as well as the Northeast Corner of Section 28. Point corresponds with local lines of possession. Set rebar with cap, accepted and filed new CCR.
- C-18-464 North Quarter Corner of Section 28, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Point corresponds with existing lines of possession. Accepted and filed new CCR.
- C-18-465 Northeast Corner of Section 28, Township 28 North, Range 20 East, found 5/8" Iron Pin with illegible plastic cap, corresponds with local lines of possession. No existing CCR filed. Acknowledged corner and filed new CCR.
- C-18-466 North Quarter Corner of Section 27, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Point corresponds with existing lines of possession. Accepted and filed new CCR.
- C-18-467 Northeast Corner of Section 27, Township 28 North, Range 20 East, calculated corner using proportionate measurements from Southeast corner of Section 27 and Northeast corner of Section 26, adjusted location in favor of lines of possession. Set rebar with cap and filed new CCR.
- C-18-468 East Quarter Corner of Section 27, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Accepted and filed new CCR.
- 9001 Center of Section 27, Township 28 North, Range 20 East, calculated point only. No monument found.

Historical Letter & Written Report
Page 4 of 6

DETAILED NARRATIVE OF SECTION CORNER ASSESSMENT (cont.)

- C-18-469 East Quarter Corner of Section 28, Township 28 North, Range 20 East, found 1/2" Iron Pin w/ illegible plastic cap. No existing references. Accepted corner and filed new CCR.
- 9002 Center of Section 28, Township 28 North, Range 20 East, calculated point only. No monument found.
- C-18-470 West Quarter Corner of Section 28, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Point corresponds with existing lines of possession. Accepted and filed new CCR.
- C-18-471 Southwest Quarter Corner of Section 28, Township 28 North, Range 20 East, Found 1/2" Iron Pin, 4" below surface. No existing references. Point corresponds with existing lines of possession. Acknowledged corner and filed new CCR.
- C-18-472 South Quarter Corner of Section 28, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Accepted and filed new CCR.
- C-18-473 Southeast Quarter Corner of Section 28, Township 28 North, Range 20 East, found MAG Nail. Point corresponds with CCR filed by William McKinley Thomas, III, PLS No. 1342 on April 6, 2006, acknowledged corner and filed new CCR.
- C-18-474 South Quarter Corner of Section 27, Township 28 North, Range 20 East, found MAG Nail. Point corresponds with CCR filed by William McKinley Thomas, III, PLS No. 1342 on April 6, 2006, acknowledged corner and filed new CCR.
- C-18-475 Southeast Corner of Section 27, Township 28 North, Range 20 East, found 3/8" Iron Pin, no existing CCR. Point corresponds with existing lines of possession. Accepted corner and filed new CCR.
- C-18-476 East Quarter Corner of Section 34, Township 28 North, Range 20 East, found 1" square rod, point corresponds with existing lines of possession. Accepted corner and filed new CCR.
- 9004 Center of Section 34, Township 28 North, Range 20 East, calculated point only. No monument found.
- C-18-477 East Quarter Corner of Section 33, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Accepted and filed new CCR.
- 9003 Center of Section 33, Township 28 North, Range 20 East, calculated point only. No monument found.

Historical Letter & Written Report
Page 5 of 6

DETAILED NARRATIVE OF SECTION CORNER ASSESSMENT (cont.)

- C-18-478 West Quarter Corner of Section 33, Township 28 North, Range 20 East, found 3/8" iron pin. Point corresponds with CCR filed by William McKinley Thomas, III, PLS No. 1342 on January 30, 2003, acknowledged corner and filed new CCR.
- C-18-479 Southwest Quarter Corner of Section 33, Township 28 North, Range 20 East, found 40d nail. Point corresponds with CCR filed by George Michael Finnell, LS 1107 on December 03, 2002. Point corresponds with existing lines of possession. Replaced 40d nail with 3/8" rebar w/ cap. Acknowledged corner and filed new CCR.
- C-18-480 South Quarter Corner of Section 33, Township 28 North, Range 20 East, set rebar w/ cap at split and on line between section corners. Accepted and filed new CCR.
- C-18-481 Southeast Quarter Corner of Section 33, Township 28 North, Range 20 East, set rebar w/ cap at proportionate distance on line and between Southwest corner of Section 33 and South Quarter corner of Section 34. Location corresponds with existing lines of possession. Accepted location and filed new CCR.
- C-18-482 South Quarter Corner of Section 34, Township 28 North, Range 20 East, found 1" steel anchor bolt. No references. Accepted corner and filed new CCR.
- C-18-483 Southeast Corner of Section 34, Township 28 North, Range 20 East, set rebar w/ cap at proportionate distance between South Quarter corner of Section 34 and the Southwest corner of Section 33 as well as the East Quarter corner of Section 34. Location corresponds with existing lines of possession. Accepted location and filed new CCR.

Historical Letter & Written Report
Page 6 of 6

PLS	KAI		OKLAHOMA DEPARTMENT OF TRANSPORTATION SURVEY DIVISION SURVEY DATA SHEET (3) SMO <u>5076 (1)</u> PROJECT NO. <u>29068(04)</u> SHEET NO. <u>23</u>
DRAWN	JDI		
CHECKED	KAI		
APPROVED	KAI		
CREW	ISAACS		