

REVISIONS		
NO.	DESCRIPTION	DATE


## LIGHT POLE SCHEDULE

LOCATION				FOOTING			POLE ASSEMBLY							REMARKS		
SHEET NO.	POLE NO.	STATION (CTR. OR REF. LINE)	DISTANCE FROM FACE OF CURB FT	TYPE	CONC. CY	STL. LB	B.BASE DESIGN NO.	MTG. HT. FT	ARM NO. 1 FT	ARM NO. 2 FT	NO./WATTS EA/WATT	IES DIST. TYPE	1/C NO 12 AWG TYPE THW FT		LIGHTNING ARRESTOR EA	
T3	1	161+50 RT (CLEVELAND)	8	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T3	2	161+65 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T3	3	162+60 RT (CLEVELAND)	6	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T3	4	162+80 LT (CLEVELAND)	8	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T3	5	163+80 RT (CLEVELAND)	6	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T3	6	164+05 LT (CLEVELAND)	13	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T3	7	165+25 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	8	166+75 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200	1	DECORATIVE POLES & LUMINAIRES	
T4	9	168+25 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	10	169+75 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	11	169+75 RT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	12	171+25 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	13	171+25 RT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T4	14	172+65 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	15	174+25 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200	1	DECORATIVE POLES & LUMINAIRES	
T4	16	175+85 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	17	177+45 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	18	179+05 CL (CLEVELAND)	CENTER	GMF24X60	0.58	33.4	(1)	30	8	8	2 - 136	MS4	200		DECORATIVE POLES & LUMINAIRES	
T4	19	180+25 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	20	180+25 RT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	21	181+35 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	22	181+35 RT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100		DECORATIVE POLES & LUMINAIRES	
T4	23	182+45 RT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
T4	24	182+55 LT (CLEVELAND)	5	GMF24X60	0.58	33.4	(1)	30	8	N/A	1 - 136	MS4	100	1	DECORATIVE POLES & LUMINAIRES	
<b>TOTALS</b>					<b>13.92</b>	<b>801.60</b>			<b>24-30' MT POLES &amp; 8' LMA</b>			<b>32-136</b>		<b>3200</b>	<b>9</b>	


(1) - THIS ITEM PROVIDED BY THE MANUFACTURER. COST TO BE INCLUDED IN THE PRICE BID FOR THE POLES.

## SERVICE POLE SCHEDULE

SHEET NO.	SERVICE POLE NO.	LOCATION			CONTROLLER							METER EQUIP.	DISCONNECT SWITCH 100 AMP	REMARKS
		STATION (CTR. OR REF. LINE)	TYPE	SECONDARY VOLTAGE & NO. PHASE	RATING			CIRCUIT LOADING						
					QUANTITY	NO. OF CONTACTS	AMP RATE OF CONTACTS	CIRCUIT ID	EST. AMPS PER CIR.	MIN. FUSE AMP/CIR.	VOLTAGE DROP %			
T3	1	STA. 165+25 50' LT	UG/1	480-1	1	2	60	A	16	25	1.93	NM	YES	

  
 R. WAYNE RUSSELL, P.E. # 16030  
 C.A. # 1160, RENEWAL 06-30-17

12-12-16  
 DATE



Traffic Engineering Consultants, Inc.  
 6000 S. Western, Suite 300 - Oklahoma City, OK 73139,  
 Ph: 405-720-7721, Fax: 405-720-9848, Web: www.tecok.com

Design	RWR	12/14/2016
Drawn	CCC	12/14/2016



### LIGHT POLE AND SERVICE POLE SCHEDULE

Project No. R-1311B Sheet No. T1