

OKLAHOMA DEPARTMENT OF TRANSPORTATION					
FED. ROAD DIST. NO.	STATE	PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	OKLA.				
DESCRIPTION		REVISIONS		DATE	

CHECK LEVELS BENCH MARK LIST

SWO 4851(1) NAVD 88 DATUM

BM NO.	RUN 1	RUN 2	MEAN DIFF.	UNADJ. ELEV.	ADJ. ELEV.	PUBLISHED ELEV.	BENCHMARK DESCRIPTION
BM 1				681.660	681.66	BM 1	60d NAIL IN 12" LOCUST,
7400	-1.890	-1.890	-1.890	679.767	679.77	CP 7400	3/8" IRON PIN WITH ORANGE CAP,
7401	-1.570	-1.570	-1.570	678.200	678.20	CP 7401	1/2" IRON PIN WITH ALUMINUM CAP, STA. 280+37.68, 61.44' LT.
BM 2	1.340	1.340	1.340	679.540	679.54	BM 2	TOP OF RIGHT-OF-WAY MARKER, STA. 280+00.86, 64.58' LT.
BM 3	-2.880	-2.880	-2.880	676.660	676.67	BM 3	CHISELED "BOX" ON NE CORNER OF HEADWALL, STA. 285+10.21, 25.10' LT.
7402	-2.050	-2.050	-2.050	674.610	674.62	CP 7402	3/8" IRON PIN WITH ORANGE CAP, 285+45.10, 48.09' LT.
BM 4	4.270	4.270	4.270	678.880	678.89	BM 4	60d IN POWER POLE, STA. 289+61.38, 75.97' LT.
7403	-0.410	-0.410	-0.410	678.470	678.48	CP 7403	3/8" IRON PIN WITH ORANGE CAP, STA. 290+49.04, 73.37' LT.
7404	-2.190	-2.190	-2.190	676.280	676.30	CP 7404	3/8" IRON PIN WITH ORANGE CAP, STA. 295+52.54, 62.58' LT.
BM 5	-0.940	-0.940	-0.940	675.340	675.36	BM 5	60d IN 10" LOCUST, STA. 295+78.13, 121.33' LT.
7405	-3.040	-3.040	-3.040	672.300	672.32	CP 7405	3/8" IRON PIN WITH ORANGE CAP, STA. 302+38.49, 21.85' LT.
BM 6	-6.050	-6.050	-6.050	666.250	666.28	BM 6	60d IN HACKBERRY, STA. 301+51.04, 65.10' LT.
7406	6.000	6.000	6.000	672.250	672.28	CP 7406	3/8" IRON PIN WITH ORANGE CAP, STA. 305+02.08, 22.66' RT.
BM 7	-9.420	-9.420	-9.420	662.830	662.86	BM 7	80d IN 24" LOCUST, STA. 306+10.00, 125.89' RT.
7407	7.120	7.120	7.120	669.950	669.99	CP 7407	3/8" IRON PIN WITH ORANGE CAP, STA. 310+16.73, 61.23' RT.
BM 8	6.760	6.760	6.760	676.710	676.75	BM 8	80d IN POWER POLE, STA. 310+31.75, 103.69' LT.
7408	4.850	4.850	4.850	681.560	681.60	CP 7408	3/8" IRON PIN WITH ORANGE CAP, STA. 315+27.33, 62.24' RT.
BM 9	1.150	1.150	1.150	682.710	682.75	BM 9	80d IN POWER POLE, STA. 315+27.03, 71.80' RT.
BM 10	3.810	3.810	3.810	686.520	686.57	BM 10	80d IN LOCUST, STA. 320+05.69, 104.08' RT.
7409	-0.520	-0.520	-0.520	686.000	686.05	CP 7409	1/2" IRON PIN WITH ALUMINUM CAP, STA. 319+95.62, 41.94' RT.
7410	6.040	6.040	6.040	692.040	692.11	CP 7410	3/8" IRON PIN WITH ORANGE CAP,
BM 11	1.220	1.220	1.220	693.260	693.33	BM 11	80d IN POWER POLE,

OKLAHOMA DEPARTMENT OF TRANSPORTATION			
SURVEY DIVISION			
SURVEY DATA SHEET			
PLS	DMM		
DRAWN	VKM		
CHECKED	CAC		
APPROVED	DMM		
CREW	GES, INC.	SWO 4851(1)	PROJECT NO. 28857(04) SHEET NO. S004